

Product Discontinuance Notification—PDN# 0000401575

September 01, 2026

Dear Valued Customer,

We would like to inform you that the EDS-516A and EDS-518A Series will reach its End of Life (EoL) phase, starting **January 01, 2024**.

If you need any of these products for an existing project, please contact your Moxa sales representative to place orders before the last-buy date of **June 30, 2027**. Also, please note that last-buy orders may be subject to availability.

The End of Service (EoS) date will be **January 01, 2030**. Following this date, all support services—including technical assistance, new software upgrades, and new security fixes—will no longer be available. Hardware warranty, repair, and replacement services remain subject to the standard warranty policy for these products.

Please review the details below to determine how these discontinuances will affect your products and/or operations.

Which products will reach EoL?

The following products will reach EoL. Also, see the models recommended to replace those models that will soon reach EoL, as well as when the replacement models will be available for order.

EOL	Recommended Replacement	Available for Order
EDS-516A Series	EDS-518E Series SDS-3016 Series	Available Now
EDS-518A Series	EDS-518E Series	Available Now

Applicable differences in specifications

In this table, we list the differences in specifications between the EoL products and the recommended replacement products.

Option #1

Specification	EDS-516A/518A Series (EoL)	EDS-518E Series (Replacement)
---------------	----------------------------	-------------------------------

Dimensions	94 x 135 x 142.7 mm (3.7 x 5.31 x 5.62 in)	94 x 135 x 137 mm (3.7 x 5.31 x 5.39 in)
Reset Button	N/A	Yes
Input Voltage	24 VDC, Redundant dual inputs	12/24/48/-48 VDC Redundant dual inputs
Gigabit Port	EDS-516A: N/A EDS-518A: 2*Combo ports (10/100/1000BaseT(X) or 1000BaseSFP)	4* Combo ports (10/100/1000BaseT(X) or 1000BaseSFP)
100BaseFX Ports	EDS-516A-MM-SC: 2* multi-mode SC connector EDS-516A-MM-ST: 2* multi-mode ST connector EDS-518A-MM-SC: 2*multi-mode SC connector EDS-518A-MM-ST: 2* multi-mode ST connector EDS-518A-SS-SC: 2 *single-mode SC connector EDS-518A-SS-SC-80: 2*single-mode SC Connector, 80 km	EDS-518E-MM-SC-4GTXSFP: 2* multi-mode SC connector EDS-518E-MM-ST-4GTXSFP: 2* multi-mode ST connector EDS-518E-SS-SC-4GTXSFP: 2* single-mode SC connector
Certifications	EN 60950-1, UL 508, EN 55032/24, CISPR 32, FCC Part 15B Class A, Marine (DNV-GL), Hazardous Locations (ATEX, Class I Division 2)	UL 508, EN 60950-1 (LVD), EN 61000-6-2/-6-4, CISPR 32, FCC Part 15B Class A, Marine (DNV-GL, LR, ABS, NK), Power Substation (IEC 61850-3, IEEE 1613), Traffic Control (NEMA TS2), Hazardous Locations (ATEX, Class I Division 2)

Option #2

Specification	EDS-516A (EoL)	SDS-3016 Series (Replacement)
Dimensions	94 x 135 x 142.7 mm (3.7 x 5.31 x 5.62 in)	36 x 135 x 111 mm (1.42 x 5.32 x 4.37 in)
Reset Button	N/A	Yes
Input Voltage	24 VDC, Redundant dual inputs	12/24/48/-48 VDC

		Redundant dual inputs
Gigabit Port	N/A	2* 10/100/1000BaseT(X)
Certifications	EN 60950-1, UL 508, EN 55032/24, CISPR 32, FCC Part 15B Class A, Marine (DNV), Hazardous Locations (ATEX, Class I Division 2)	EN 55032/35, EN 61000-6-2/-6-4, CISPR 32, FCC Part 15B Class A, EN 62368-1, UL 61010-2-201

Please note that all service rules (e.g., warranty) still apply to the EoL products.

If you have any questions, please contact your regional sales representative.