

PWR-310電源モジュールシリーズ

RKS-G4000-PLモジュール型マネージドスイッチ用電源モジュール



機能とメリット

- 多様な設置方向に対応する回転式设计
- ホットスワップ対応
- 柔軟な導入を可能にする広い電源入力範囲

認証



製品紹介

PWR-310電源モジュールシリーズは、MoxaのRKS-G4000-PLシリーズスイッチ向けに設計されています。この電源モジュールにより、対応スイッチは12/24/48 VDCまたは110/220 VDC/VACを使用できます。

仕様

Power Parameters	
Connection	2 removable 4-contact terminal block(s)
Input Voltage	PWR-310-HV-P: 110/220 VDC/VAC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices) PWR-310-LV-P: 12/24/48 VDC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices) PWR-310-HVA: 110/220 VAC for the switch system PWR-310-HV: 110/220 VDC/VAC for the switch system PWR-310-LV: 12/24/48 VDC for the switch system
Operating Voltage	PWR-310-LV/PWR-310-LV-P models: 10.8 to 72 VDC PWR-310-HV: 88 to 300 VDC, 85 to 264 VAC PWR-310-HVA: 85 to 264 VAC PWR-310-HV-P models: 88 to 300VDC,85 to 264 VAC PoE models: 46 to 57 VDC (for the PoE system)
Input Current	PWR-310-LV/PWR-310-LV-P models: Max.7.28A@12VDC Max.3.08A@24VDC Max.1.52A@48VDC PWR-310-HV/PWR-310-HV-P models: Max.0.67A@110VDC Max.0.33A@220VDC Max.0.79A@110VAC

	Max.0.35A@220VAC PWR-310-HVA models: Max.0.8A@110VAC Max.0.35A@220VAC EPS (PoE modelsonly): Max.12A@48to57VDC 48 to 57 VDC, 12 A (max.)
Overload Current Protection	Supported
Reverse Polarity Protection	Supported

Physical Characteristics

Dimensions	PWR-310-HV-P: 377.8 x 54.5 x 40.5 mm (14.87 x 2.15 x 1.59 in) PWR-310-LV-P: 377.8 x 54.5 x 40.5 mm (14.87 x 2.15 x 1.59 in) PWR-310-HVA: 377.8 x 54.5 x 40.5 mm (14.87 x 2.15 x 1.59 in) PWR-310-HV: 377.8 x 54.5 x 40.5 mm (14.87 x 2.15 x 1.59 in) PWR-310-LV: 377.8 x 54.5 x 40.5 mm (14.87 * 2.15 x 1.59 in)
Weight	PWR-310-HV-P: 845 g (1.86 lb) PWR-310-LV-P: 830 g (1.83 lb) PWR-310-HVA: 861 g (1.90 lb) PWR-310-HV: 854 g (1.88 lb) PWR-310-LV: 854 g (1.88 lb)

MTBF

Time	PWR-310-HV-P: 5,480,917 hrs PWR-310-LV-P: 12,412,949 hrs PWR-310-HVA: 5,536,383 hrs PWR-310-HV: 5,536,383 hrs PWR-310-LV: 12,700,198 hrs
Standards	Telcordia (Bellcore), GB

Environmental Limits

Operating Temperature	The operating temperature is dependent on the RKS-G4000-PL switch the module is installed in. Please refer to the respective RKS-G4000-PL Series datasheet/QIG for more information.
Storage Temperature	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (non-condensing)

Warranty

Warranty Period	5 years
Details	See www.moxa.com/jp/warranty

注文情報

Model Name	Input Voltage	Operating Voltage	Supported Series
PWR-310-LV	12/24/48 VDC	10.8 to 72 VDC	RKS-G4028-PL Series RKS-G4028-PL-L3 Series RKS-G4030-PL Series RKS-G4030-PL-L3 Series
PWR-310-LV-P	12/24/48 VDC 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)	10.8 to 72 VDC (53 to 57 VDC is recommended for PoE+ devices)	RKS-G4028-PL Series RKS-G4028-PL-L3 Series RKS-G4030-PL Series RKS-G4030-PL-L3 Series
PWR-310-HVA	110/220 VDC/VAC	85 to 264 VAC	RKS-G4028-PL Series RKS-G4028-PL-L3 Series RKS-G4030-PL Series RKS-G4030-PL-L3 Series

Model Name	Input Voltage	Operating Voltage	Supported Series
PWR-310-HV	110/220 VAC	88 to 300 VDC, 85 to 264 VAC	RKS-G4028-PL Series RKS-G4028-PL-L3 Series RKS-G4030-PL Series RKS-G4030-PL-L3 Series
PWR-310-HV-P	110/220 VDC/VAC 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)	88 to 300 VDC, 85 to 264 VAC (53 to 57 VDC is recommended for PoE+ devices)	RKS-G4028-PL Series RKS-G4028-PL-L3 Series RKS-G4030-PL Series RKS-G4030-PL-L3 Series

© Moxa Inc. All rights reserved.2026年6月11日更新。

Moxa Inc.の明白な許可を written で取得しない限り、本書およびその一部の複製や使用はいかなる方法やいかなる場合でも許可されません。製品の仕様は予告なく変更されることがあります。最新の製品情報については当社のWebサイトをご覧ください。