

MGate 5114 系列

1 埠 Modbus RTU/ASCII/TCP/IEC 101 轉 IEC 104 閘道器



特色與優點

- Modbus RTU/ASCII/TCP、IEC 60870-5-101、IEC 60870-5-104 之間的通訊協定轉換
- 支援 IEC 60870-5-101 主控裝置/從屬裝置 (平衡/非平衡)
- 支援 IEC 60870-5-104 用戶端/伺服器
- 支援 Modbus RTU/ASCII/TCP master/client and slave/server
- 透過網頁式設定精靈輕鬆配置
- 狀態監控和故障保護，可輕鬆維護
- 內建流量監控/診斷資訊，便於故障排除與雲端數據傳輸，以及成本評估和分析
- 用於配置備份/複製和事件日誌的 microSD 卡，以及雲端連網中斷時的數據緩衝
- 輕鬆佈線的內建乙太網路串接
- 備援雙直流電源輸入和繼電器輸出
- 提供 -40 至 75°C 寬溫度操作型號可供選用
- 串列內建埠 2kV 隔離保護

認證



簡介

MGate 5114 是工業乙太網路閘道器，配備 2 個乙太網路連接埠和 1 個 RS-232/422/485 串列埠，適用於 Modbus RTU/ASCII/TCP、IEC 60870-5-101 和 IEC 60870-5-104 網路通訊。透過整合常用的電源通訊協定，MGate 5114 提供滿足現場裝置使用不同通訊通訊協定連接到電源 SCADA 系統時出現的各種條件所需的彈性。若要將 Modbus 或 IEC 60870-5-101 裝置整合到 IEC 60870-5-104 網路，請將 MGate 5114 做為 Modbus 主控裝置/用戶端或 IEC 60870-5-101 主控裝置，藉以收集數據並與 IEC 60870-5-104 系統交換數據。

透過 Web 主控台 輕鬆配置

MGate 5114 系列隨附有插圖的快速安裝指南，配置更便利。透過快速安裝，只要幾個步驟即可輕鬆存取通訊協定轉換模式，並完成配置。

Modbus RTU/ASCII/TCP 通訊協定流量監控

MGate 5114 系列閘道器支援 Modbus RTU/ASCII/TCP、IEC 60870-5-101 和 IEC 60870-5-104 通訊協定流量監控，故障排除更容易，尤其在安裝階段。值得一提的是，可以在常用的故障排除工具 Wireshark 中查看流量日誌。使用此項功能可以輕鬆分析流量以確定問題的根本原因。

維護功能

MGate 5114 閘道器支援系統日誌功能，可記錄 MGate 中的事件；使用者可以透過 Web 主控台從遠端輕鬆檢閱日誌數據。閘道器也支援狀態監控和失效防護功能。裝置中斷連線或無回應時，狀態監控功能會通知 PSCADA 系統，PSCADA 系統取得每台終端裝置的狀態，並發出警報通知操作員。

規格

Ethernet Interface

10/100BaseT(X) Ports (RJ45 connector)	2 Auto MDI/MDI-X connection
Magnetic Isolation Protection	1.5 kV (built-in)

Ethernet Software Features

Industrial Protocols	Modbus TCP Client (Master) Modbus TCP Server (Slave) IEC 60870-5-104 Client IEC 60870-5-104 Server
Configuration Options	Web Console (HTTP/HTTPS) Device Search Utility (DSU) Telnet Console
Management	ARP DHCP Client DNS HTTP HTTPS SMTP SNMP Trap SNMPv1/v2c/v3 TCP/IP Telnet SSH UDP NTP Client
MIB	RFC1213, RFC1317
Time Management	NTP Client

Security Functions

Authentication	Local database
Encryption	HTTPS AES-128 AES-256 SHA-256
Security Protocols	SNMPv3 SNMPv2c Trap HTTPS (TLS 1.3)

Serial Interface

Console Port	RS-232 (TxD, RxD, GND), 8-pin RJ45 (115200, n, 8, 1)
No. of Ports	1
Connector	DB9 male
Serial Standards	RS-232/422/485
Baudrate	50 bps to 921.6 kbps
Data Bits	7, 8
Parity	Even Mark None Odd Space
Stop Bits	1, 2
Flow Control	RTS Toggle (RS-232 only) RTS/CTS
RS-485 Data Direction Control	Automatic Data Direction Control (ADDC)
Pull High/Low Resistor for RS-485	1 kilo-ohm, 150 kilo-ohms

Terminator for RS-485	120 ohms
Isolation	2 kV (built-in)
Serial Signals	
RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	Tx+, Tx-, Rx+, Rx-, GND
RS-485-2w	Data+, Data-, GND
RS-485-4w	Tx+, Tx-, Rx+, Rx-, GND
Serial Software Features	
Industrial Protocols	Modbus RTU/ASCII Master Modbus RTU/ASCII Slave IEC 60870-5-101 Master (Balanced/Unbalanced) IEC 60870-5-101 Slave (Balanced/Unbalanced)
Configuration Options	Serial Console
Modbus RTU/ASCII	
Mode	Master, Slave
Functions Supported	1, 2, 3, 4, 5, 6, 15, 16, 23
Max. No. of Commands	128
Modbus TCP	
Mode	Client (Master), Server (Slave)
Functions Supported	1, 2, 3, 4, 5, 6, 15, 16, 23
Max. No. of Client Connections	32
Max. No. of Server Connections	32
Max. No. of Commands	128
IEC 60870-5-104	
Mode	Client Server
Max. No. of Client Connections	32
Max. No. of Server Connections	32
Max. No. of Information Objects	2000 points
IEC 60870-5-101	
Mode	Master (Balanced/Unbalanced) Slave (Balanced/Unbalanced)
Max. No. of Master Connections	1
Max. No. of Slave Connections	1 (Balanced), 31 (Unbalanced)
Max. No. of Information Objects	2000 points
Memory	
microSD Slot	Up to 32 GB (SD 2.0 compatible)

Power Parameters

Input Voltage	12 to 48 VDC
Input Current	455 mA @ 12 VDC
Power Connector	Screw-fastened Euroblock terminal

Relays

Contact Current Rating	Resistive load: 2 A @ 30 VDC
------------------------	------------------------------

Physical Characteristics

Housing	Metal
IP Rating	IP30
Dimensions	36 x 105 x 140 mm (1.42 x 4.14 x 5.51 in)
Weight	507 g (1.12 lb)

Environmental Limits

Operating Temperature	MGate 5114: 0 to 60°C (32 to 140°F) MGate 5114-T: -40 to 75°C (-40 to 167°F)
Storage Temperature (package included)	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (non-condensing)

Standards and Certifications

EMC	EN 55032/35
EMI	CISPR 32, FCC Part 15B Class B
EMS	IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 10 V/m IEC 61000-4-8 PFMF
Safety	EN 62368-1 UL 508
Hazardous Locations	ATEX Class I Division 2 IECEx
Freefall	IEC 60068-2-32
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6 IEC 60068-2-64

MTBF

Time	1,140,815 hrs
Standards	Telcordia SR332

Warranty


Warranty Period	5 years
Details	See www.moxa.com/tw/warranty

Package Contents

Device	1 x MGate 5114 Series gateway
Cable	1 x RJ45-to-DB9 console cable
Installation Kit	1 x DIN-rail kit
Documentation	1 x quick installation guide 1 x warranty card

尺寸

單位：公釐（英吋）



訂購資訊

Model Name	Operating Temp.
MGate 5114	0 to 60°C
MGate 5114-T	-40 to 75°C

配件（選購）

Cables

CBL-F9M9-150	DB9 female to DB9 male serial cable, 1.5 m
CBL-F9M9-20	DB9 female to DB9 male serial cable, 20 cm
CBL-RJ45F9-150	8-pin RJ45 to DB9 female serial cable, 1.5m
CBL-RJ45SF9-150	8-pin RJ45 to DB9 female serial cable with shielding, 1.5m

Connectors

Mini DB9F-to-TB	DB9 female to terminal block connector
-----------------	--

Power Cords

CBL-PJTB-10	Non-locking barrel plug to bare-wire cable
-------------	--

Mounting Kits

DK-25-01	DIN-rail mounting kit, 2 screws
WK-36-02	DIN-rail/wall-mounting kit, 2 plates, 6 screws

© Moxa Inc. 版權所有.2025 年 5 月 27 日更新。

未經 Moxa Inc. 明確書面許可，不得以任何方式複製或使用本文件及其任何部分。產品規格如有變更，恕不另行通知。請至本公司官網了解最新的產品資訊。