

PM-7200モジュールシリーズ

PTシリーズラックマウントイーサネットスイッチ用のギガビットおよび高速イーサネットモジュール



機能とメリット

- -40～85°Cの広範囲動作温度
- IEC 61850-3およびIEEE 1613準拠

認証



製品紹介

PM-7200モジュールシリーズには、PTシリーズラックマウントイーサネットスイッチ用のギガビットおよび高速イーサネットモジュールが含まれています。IEEE 1588インターフェースモジュールは、ハードウェアベースのPTP機能を提供し、ネットワーク全体で正確な時間同期を実現します。

仕様

Ethernet Software Features

Time Management	PTP models: IEEE 1588 PTP v1/v2 (hardware-based)
Redundancy Protocols	PM-7200-PHR-PTP Series: HSR, PRP

Ethernet Interface

Combo Ports (10/100/1000BaseT(X) or 1000BaseSFP)	PM-7200-2GTXSFP: 2 PM-7200-4GTXSFP: 4
10/100/1000BaseT(X) Ports PRP/HSR Ports	PM-7200-4GTX-PHR-PTP: 2
100/1000BaseSFP PRP/HSR Ports	PM-7200-4GSFP-PHR-PTP: 2
10/100/1000BaseT(X) Ports (RJ45 connector)	PM-7200-4GTX-PHR-PTP: 2
100/1000BaseSFP Ports	PM-7200-4GSFP-PHR-PTP: 2
10/100BaseT(X) Ports (RJ45 connector)	PM-7200-2TX Series: 2 PM-7200-4TX Series: 4 PM-7200-8TX: 8
10/100BaseT(X) Ports (M12 D-coded 4-pin female connector)	PM-7200-4M12: 4
100BaseSFP Slots	PM-7200-8SFP: 8
100BaseFX Ports (multi-mode SC connector)	PM-7200-1MSC: 1 PM-7200-2MSC Series: 2 PM-7200-4MS Series: 4 PM-7200-6MSC: 6

100BaseFX Ports (multi-mode ST connector)	PM-7200-1MST: 1 PM-7200-2MST Series: 2 PM-7200-4MST Series: 4 PM-7200-6MST: 6																																																			
100BaseFX Ports (single-mode SC connector)	PM-7200-2SSC Series: 2 PM-7200-4SSC2TX: 4 PM-7200-6SSC: 6																																																			
100BaseFX Ports, Multi-Mode MTRJ Connector	PM-7200-8MTRJ: 8																																																			
PPS Output, BNC Connector	PM-7200-1BNC2MST-PTP: 1																																																			
Optical Fiber	<table border="1"> <thead> <tr> <th colspan="2" rowspan="2"></th> <th colspan="3">100BaseFX</th> </tr> <tr> <th colspan="2">Multi-Mode</th> <th>Single-Mode</th> </tr> <tr> <th rowspan="2">Fiber Cable Type</th> <th rowspan="2">OM1</th> <th>50/125 μm</th> <th colspan="2">G.652</th> </tr> <tr> <th>800 MHz x km</th> <th colspan="2"></th> </tr> </thead> <tbody> <tr> <td colspan="2">Typical Distance</td> <td>4 km</td> <td>5 km</td> <td>40 km</td> </tr> <tr> <td rowspan="3">Wavelength</td> <td>Typical (nm)</td> <td colspan="2">1300</td> <td>1310</td> </tr> <tr> <td>TX Range (nm)</td> <td colspan="2">1260 to 1360</td> <td>1280 to 1340</td> </tr> <tr> <td>RX Range (nm)</td> <td colspan="2">1100 to 1600</td> <td>1100 to 1600</td> </tr> <tr> <td rowspan="4">Optical Power</td> <td>TX Range (dBm)</td> <td colspan="2">-10 to -20</td> <td>0 to -5</td> </tr> <tr> <td>RX Range (dBm)</td> <td colspan="2">-3 to -32</td> <td>-3 to -34</td> </tr> <tr> <td>Link Budget (dB)</td> <td colspan="2">12</td> <td>29</td> </tr> <tr> <td>Dispersion Penalty (dB)</td> <td colspan="2">3</td> <td>1</td> </tr> </tbody> </table> <p>Note: When connecting a single-mode fiber transceiver, we recommend using an attenuator to prevent damage caused by excessive optical power. Note: Compute the “typical distance” of a specific fiber transceiver as follows: Link budget (dB) > dispersion penalty (dB) + total link loss (dB).</p>			100BaseFX			Multi-Mode		Single-Mode	Fiber Cable Type	OM1	50/125 μm	G.652		800 MHz x km			Typical Distance		4 km	5 km	40 km	Wavelength	Typical (nm)	1300		1310	TX Range (nm)	1260 to 1360		1280 to 1340	RX Range (nm)	1100 to 1600		1100 to 1600	Optical Power	TX Range (dBm)	-10 to -20		0 to -5	RX Range (dBm)	-3 to -32		-3 to -34	Link Budget (dB)	12		29	Dispersion Penalty (dB)	3		1
				100BaseFX																																																
		Multi-Mode		Single-Mode																																																
Fiber Cable Type	OM1	50/125 μm	G.652																																																	
		800 MHz x km																																																		
Typical Distance		4 km	5 km	40 km																																																
Wavelength	Typical (nm)	1300		1310																																																
	TX Range (nm)	1260 to 1360		1280 to 1340																																																
	RX Range (nm)	1100 to 1600		1100 to 1600																																																
Optical Power	TX Range (dBm)	-10 to -20		0 to -5																																																
	RX Range (dBm)	-3 to -32		-3 to -34																																																
	Link Budget (dB)	12		29																																																
	Dispersion Penalty (dB)	3		1																																																

Warranty

Warranty Period	5 years
Details	See www.moxa.com/jp/warranty

Package Contents

Device	1 x PM-7200 Series module
Documentation	1 x warranty card 1 x product certificates of quality inspection, Simplified Chinese 1 x product notice, Simplified Chinese

注文情報

Model Name	1000 Mbps	100 Mbps	PPS Output	Hardware-Based IEEE 1588 PTP V2	PRP/HSR	Operating Temp.
PM-7200-1MSC	-	1 x 100BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-1MST	-	1 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-2GTXSFP	2 x combo port, 10/100/1000BaseT (X) or 1000BaseSFP	-	-	-	-	-45 to 85°C

Model Name	1000 Mbps	100 Mbps	PPS Output	Hardware-Based IEEE 1588 PTP V2	PRP/HSR	Operating Temp.
PM-7200-2MSC	-	2 x 100BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-2MSC4TX	-	4 x 10/100BaseT (X) 2 x 100BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-2MST	-	2 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-2MST4TX	-	4 x 10/100BaseT (X) 2 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-2SSC	-	2 x 100BaseFX, single-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-2SSC4TX	-	4 x 10/100BaseT (X) 2 x 100BaseFX, single-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-4GTXSFP	4 x combo port, 10/100/1000BaseT (X) or 1000BaseSFP	-	-	-	-	-45 to 85°C
PM-7200-4M12	-	4 x 10/100BaseT (X), M12 connectors	-	-	-	-45 to 85°C
PM-7200-4MSC2TX	-	2 x 10/100BaseT (X) 4 x 100BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-4MST2TX	-	2 x 10/100BaseT (X) 4 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-4SSC2TX	-	2 x 10/100BaseT (X) 4 x 100BaseFX, single-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-6MSC	-	6 x 100BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-6MST	-	6 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-6SSC	-	6 x 100BaseFX, single-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-8SFP	-	8 x 100BaseFX	-	-	-	-45 to 85°C
PM-7200-8TX	-	8 x 10/100BaseT (X)	-	-	-	-45 to 85°C
PM-7200-1BNC2MST-PTP	-	2 x 100BaseFX, multi-mode, ST connector	1 x BNC connector	-	-	-45 to 85°C

Model Name	1000 Mbps	100 Mbps	PPS Output	Hardware-Based IEEE 1588 PTP V2	PRP/HSR	Operating Temp.
PM-7200-8MTRJ	-	8 x 100BaseFX, multi-mode, MTRJ connector	-	-	-	-45 to 85°C
PM-7200-4TX-PTP	-	4 x 10/100BaseT (X)	-	P	-	-45 to 85°C
PM-7200-4MST-PTP	-	4 x 100BaseFX, multi-mode, ST connector	-	P	-	-45 to 85°C
PM-7200-4MSC-PTP	-	4 x 100BaseFX, multi-mode, SC connector	-	P	-	-45 to 85°C
PM-7200-4GTX-PHR-PTP	2 x 10/100/1000BaseT(X)	-	-	P	2 x 10/100/1000BaseT(X) PRP/HSR ports	-45 to 85°C
PM-7200-4GSFP-PHR-PTP	2 x 100/1000BaseSFP	-	-	P	2 x 100/1000-BaseSFP PRP/HSR ports	-45 to 85°C

アクセサリ（別売）

SFP Modules

SFP-1FELLC-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1FEMLC-T	SFP module with 1 100Base multi-mode with LC connector for 4 km transmission, -40 to 85°C operating temperature
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G10BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G20ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G20ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G20BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G20BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G40ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G40ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G40BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G40BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1GEZXLC	SFP module with 1 1000BaseEZX port with LC connector for 110 km transmission, 0 to 60°C operating temperature
SFP-1GEZXLC-120	SFP module with 1 1000BaseEZX port with LC connector for 120 km transmission, 0 to 60°C operating temperature

SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature
SFP-1GLHXLC	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature
SFP-1GLHXLC-T	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1GLSXLC	SFP module with 1 1000BaseLSX port with LC connector for 500 m transmission, 0 to 60°C operating temperature
SFP-1GLSXLC-T	SFP module with 1 1000BaseLSX port with LC connector for 500 m transmission, -40 to 85°C operating temperature
SFP-1GLXLC	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature
SFP-1GLXLC-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature
SFP-1GSXLC	SFP module with 1 1000BaseSX port with LC connector for 300/550 m transmission, 0 to 60°C operating temperature
SFP-1GSXLC-T	SFP module with 1 1000BaseSX port with LC connector for 300/550 m transmission, -40 to 85°C operating temperature
SFP-1GZXLC	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature
SFP-1GZXLC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature

© Moxa Inc. All rights reserved. 2020年6月2日更新。

Moxa Inc.の明白な許可を画面で取得しない限り、本書およびその一部の複製や使用はいかなる方法やいかなる場合でも許可されません。製品の仕様は予告なく変更されることがあります。最新の製品情報については当社のWebサイトをご覧ください。