

RM-G4000-PLモジュールシリーズ

RKS-G4000-PLモジュール型マネージドスイッチ用イーサネットモジュール



機能とメリット

- 動作温度範囲-40～75℃
- IEC 61850-3およびIEEE 1613準拠
- ホットスワップ対応

認証



製品紹介

RM-G4000-PLモジュールシリーズは、IEC 61850-3準拠のRKS-G4000-PLシリーズラックマウントイーサネットスイッチ向けに特別に設計され、高密度ギガビット接続を提供します。各モジュールは、10/100/1000BaseT(X)銅線、100/1000BaseSFPファイバ、IEEE 802.3bt PoEなど、多様なインターフェースオプションを備えた最大8つのギガビットポートをサポートします。ミッションクリティカルな環境向けに設計されたRM-G4000-PLシリーズは、ポートあたり最大90 W（モジュールあたり240 Wの電力容量）の超高容量PoE機能により、高出力エッジデバイスを余裕を持って駆動します。

仕様

Ethernet Interface	
10/100/1000BaseT(X) Ports (RJ45 connector)	RM-G4000-PL-8GTX: 8
100/1000BaseSFP Ports	RM-G4000-PL-8GSFP: 8
PoE Ports (10/100/1000BaseT(X), RJ45 connector)	RM-G4000-PL-8GPoE: 8 Note: The PoE function of the RM-G4000-PL-8GPoE module is only available when used with RKS-G4000-PL PoE models.
Note	The RM-G4000-PL series modules support full-duplex communication only; half-duplex mode is not supported.
Power Parameters	
Power Consumption	RM-G4000-PL-8GSFP: 10.42 W (max.) RM-G4000-PL-8GTX: 6.05 W (max.) RM-G4000-PL-8GPoE: 6.5 W (max.)
Physical Characteristics	
Weight	RM-G4000-PL-8GSFP: 505 g (1.11 lb) RM-G4000-PL-8GTX: 438 g (0.97 lb) RM-G4000-PL-8GPoE: 596 g (1.314 lb)
MTBF	
Time	RM-G4000-PL-8GSFP: 5,828,713 hrs RM-G4000-PL-8GTX: 11,847,571 hrs RM-G4000-PL-8GPoE: 3,832,500 hrs
Standards	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
Details	See www.moxa.com/jp/warranty

Package Contents

Device	1 x RM-G4000-PL Series module
Documentation	1 x warranty card

注文情報

Model Name	10/100/1000BaseT(X) Ports	100/1000BaseSFP Ports
RM-G4000-PL-8GSFP	–	8
RM-G4000-PL-8GTX	8	–
RM-G4000-PL-8GPoE	8 (IEEE 802.3bt PoE)	–

アクセサリ（別売）

SFP Modules

SFP-1FELLC-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1FEMLC-T	SFP module with 1 100Base multi-mode, LC connector for 2/4 km transmission, -40 to 85°C operating temperature
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G10BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G20ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G20ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G20BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G20BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G40ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G40ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G40BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G40BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1GEZXLC	SFP module with 1 1000BaseEZX port with LC connector for 110 km transmission, 0 to 60°C operating temperature
SFP-1GEZXLC-120	SFP module with 1 1000BaseEZX port with LC connector for 120 km transmission, 0 to 60°C operating temperature

SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature
SFP-1GLHXLC	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature
SFP-1GLHXLC-T	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1GLSXLC	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, 0 to 60°C operating temperature
SFP-1GLSXLC-T	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, -40 to 85°C operating temperature
SFP-1GLXLC	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature
SFP-1GLXLC-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature
SFP-1GSXLC	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, 0 to 60°C operating temperature
SFP-1GSXLC-T	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, -40 to 85°C operating temperature
SFP-1GZXLC	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature
SFP-1GZXLC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1GTXRJ45-T	SFP module with 1 1000BaseT port with RJ45 connector for 100 m transmission, -40 to 75°C operating temperature

© Moxa Inc. All rights reserved.2026年5月22日更新。

Moxa Inc.の明白な許可を書面で取得しない限り、本書およびその一部の複製や使用はいかなる方法やいかなる場合でも許可されません。製品の仕様は予告なく変更されることがあります。最新の製品情報については当社のWebサイトをご覧ください。