

UPort 1100 系列

1 埠 RS-232、RS-422/485 與 RS-232/422/485 USB 轉串列轉換器



特色與優點

- 快速資料傳輸，最高傳輸率達 921.6 Kbps
- 為 Windows、macOS、Linux 和 WinCE 提供的驅動程式
- 支援 VMWare Fusion/ESXi 與 Parallels 虛擬機器
- 迷你 DB9 母轉接線端子轉接器，可便於輕鬆接線
- 指示 USB 與 TxD/RxD 活動的 LED
- 2 kV 隔離防護 (適用於“-I”型號)

認證



簡介

USB 轉串列轉換器的 UPort® 1100 系列是沒有串列埠的筆記型電腦或工作站電腦的完美配件。這些配件對於需要在現場連接不同串列裝置或為沒有標準 COM 連接埠或 DB9 接頭的裝置分隔介面轉換器的工程師非常重要。

UPort® 1100 系列可從 USB 轉換為 RS-232/422/485。所有產品均與傳統串列裝置相容，可搭配儀器與銷售點應用使用。

規格

USB Interface

Speed	12 Mbps
USB Connector	USB Type A: UPort 1110/1130/1130I/1150: USB Type B: UPort 1150I:
USB Standards	USB 2.0 compatible, USB 1.0/1.1 compliant

Serial Interface

No. of Ports	1
Connector	DB9 male
Baudrate	50 bps to 921.6 kbps
Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	None RTS/CTS XON/XOFF
Isolation	2 kV (I models)
Serial Standards	RS-232: UPort 1110 RS-422/485: UPort 1130/1130I RS-232/422/485: UPort 1150/1150I

Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	Tx+, Tx-, Rx+, Rx-, GND
RS-485-4w	Tx+, Tx-, Rx+, Rx-, GND
RS-485-2w	Data+, Data-, GND

Serial Software Features

Windows Drivers	Windows 11, 10, 8.1, 8, 7, Vista, ME, and XP Windows Server 2022, 2019, 2016, 2012 R2, 2012, 2008 R2, 2008, 2003, 2000, and NT
Linux Drivers	Kernel 6.x, 5.x, 4.x, 3.x, 2.6.x, and 2.4.x
Mac Drivers	macOS 10.12 to 10.15
Arm®-based Platform Support	Linux kernel 6.x, 5.x, and 4.x Windows 11
Virtual Machine	VMware Fusion (Windows on macOS 10.12 to 10.15) VMware ESXi (Windows 7 to 10, Windows Server 2008 R2 to 2019) VMware ESXi (Linux kernel 5 and 4) Parallels Desktop (Windows on macOS 10.12 to 10.15)
Android API	Android 3.1.x and later

Power Parameters

Input Voltage	5 VDC
Input Current	UPort 1110: 30 mA UPort 1130: 60 mA UPort 1130L: 65 mA UPort 1150: 77 mA UPort 1150L: 260 mA

Physical Characteristics

Housing	UPort 1110/1130/1130L/1150: ABS + Polycarbonate UPort 1150L: Metal
Dimensions	UPort 1110/1130/1130L/1150: 37.5 x 20.5 x 60 mm (1.48 x 0.81 x 2.36 in) UPort 1150L: 52 x 80 x 22 mm (2.05 x 3.15 x 0.87 in)
Weight	UPort 1110/1130/1130L/1150: 65 g (0.14 lb) UPort 1150L: 75 g (0.16 lb)

Environmental Limits

Operating Temperature	0 to 55°C (32 to 131°F)
Storage Temperature (package included)	-20 to 70°C (-4 to 158°F)
Ambient Relative Humidity	5 to 95% (non-condensing)

Standards and Certifications

EMC	EN 55032/35
EMI	CISPR 32, FCC Part 15B Class 1

EMS	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m IEC 61000-4-8 PFMF
Safety	UL 60950-1 (UPort 1150I)

Declaration

Green Product	RoHS, CRoHS, WEEE
---------------	-------------------

MTBF

Time	1,949,025 hrs
Standards	MIL-HDBK-217F Telcordia (Bellcore), GB

Package Contents

Device	1 x UPort 1100 Series USB-to-serial converter
Cable	UPort 1150I: 1 x USB type A male to USB type B male
Connectors	1 x Mini DB9F-to-TB (UPort 1130/1150 Models)
Documentation	1 x quick installation guide 1 x warranty card


Warranty

Warranty Period	5 years Note: Product only
Details	See www.moxa.com/tw/warranty

尺寸


UPort 1110/1130/1130I/1150

單位：公釐（英吋）



UPort 1150I

單位：公釐（英吋）



訂購資訊

Model Name	USB Interface	Serial Standards	No. of Serial Ports	Isolation	Housing Material	Operating Temp.
UPort 1110	USB 1.1	RS-232	1	–	ABS+PC	0 to 55°C
UPort 1130	USB 1.1	RS-422/485	1	–	ABS+PC	0 to 55°C
UPort 1130I	USB 1.1	RS-422/485	1	2 kV	ABS+PC	0 to 55°C
UPort 1150	USB 1.1	RS-232/422/485	1	–	ABS+PC	0 to 55°C
UPort 1150I	USB 1.1	RS-232/422/485	1	2 kV	Metal	0 to 55°C

配件（選購）

Cables

NP21101	DB25 male to DB9 female cable for RS-232 transmission, 30 cm
CBL-F9M9-20	DB9 female to DB9 male serial cable, 20 cm
CBL-F9M9-150	DB9 female to DB9 male serial cable, 1.5 m
CBL-RJ45SF9-150	8-pin RJ45 to DB9 female serial cable with shielding, 1.5m
CBL-USBA/B-100	USB Type A to USB Type B cable, 1 m

Connectors

Mini DB9F-to-TB	DB9 female to terminal block connector
ADP-RJ458P-DB9F	DB9 female to RJ45 connector

Wireless Adapters

A-ADP-RJ458P-DB9F-ABC01	DB9 female to RJ45 connector for the ABC-01 Series
-------------------------	--

Rack-Mounting Kits

WK-44-01	Rack-mounting kit, 2 L-shaped plates, 8 screws, 44 x 57.5 x 1.6 mm Applicable Models: UPort 1150I
----------	---

Wall-Mounting Kits

WK-35-01	Wall-mounting kit with 2 plates (35 x 44 x 2.5 mm) and 6 screws Applicable Models: UPort 1150I
----------	--

© Moxa Inc. 版權所有.2023 年 10 月 24 日更新。

未經 Moxa Inc. 明確書面許可，不得以任何方式複製或使用本文件及其任何部分。產品規格如有變更，恕不另行通知。請至本公司官網了解最新的產品資訊。