

# PWR-A Power Module Series

Hot-swappable power modules for the MDS-G4000-4XGS Series

## Features and Benefits

- -40 to 85°C wide operating temperature
- IEC 61850-3 and IEEE 1613 compliant



## Certifications



## Introduction

The PWR-A Power Module Series hot-swappable power modules are designed for Moxa switches. The power modules allow supported switches to use 24/48 VDC, 110/220 VAC/VDC, or 48 VDC for PoE systems.

## Specifications

### Power Parameters

Input Voltage	<p>PWR-HV-P48-A: 110/220 VDC/VAC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p> <p>PWR-LV-P48-A: 24/48 VDC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p>
Operating Voltage	<p>PWR-HV-P48-A: 88 to 300 VDC, 90 to 264 VAC for the switch system 46 to 57 VDC for PoE systems</p> <p>PWR-LV-P48-A: 18 to 72 VDC for the switch system 46 to 57 VDC for PoE systems</p>
Reverse Polarity Protection	Supported
Alarm Contact Channels	1 relay output with current carrying capacity of 2 A @ 30 VDC or 0.5 A @ 125 VAC
<b>Physical Characteristics</b>	
Weight	<p>PWR-HV-P48-A: 420 g (0.93 lb) PWR-LV-P48-A: 400 g (0.88 lb)</p>
<b>MTBF</b>	
Time	<p>PWR-HV-P48-A: 1,530,831 hrs PWR-LV-P48-A: 1,388,747 hrs</p>
Standards	Telcordia (Bellcore), GB

## Warranty

Warranty Period	5 years
Details	See <a href="http://www.moxa.com/warranty">www.moxa.com/warranty</a>

## Ordering Information

Model Name	Input Voltage	Operating Voltage	Supported Series
PWR-HV-P48-A	110/220 VDC/VAC 48 VDC for PoE systems	88-300 VDC, 90-264 VAC 46 to 57 VDC for PoE systems	MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series
PWR-LV-P48-A	24/48 VDC 48 VDC for PoE systems	18-72 VDC 46 to 57 VDC for PoE systems	MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series

© Moxa Inc. All rights reserved. Updated Nov 29, 2023.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.